

## TYRES

Product group	Tyres
Item number	10000957
Valid tyre size	320 / 60 - 12
LI / SI / PR	120 A8 / 132 A8
TL/TT	TT
Brand	BKT
Tread pattern	TR 678



## Notes and features

- The TR 678 is suitable for use on excavators and loaders as well as for the agricultural sector with its special, steel belt version.
- The tyre is characterised by its good traction and excellent self-cleaning.
- The cut-resistant tread compound reduces the risk of machinery downtimes and increases efficiency.

## Technical Informations

Item number	10000957
EAN	8903094067282
Valid tyre size	320 / 60 - 12
LI / SI / PR	120 A8 / 132 A8
TL/TT	TT
Brand	BKT
Tread pattern	TR 678
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	19.87
Recommended rim size	10.50
Maximum air pressure [bar].	4,00
Section width (mm)	328
Outer diameter of tyre [mm].	689
Stat. radius (SLR) [mm]	327
Rolling circumference [mm].	2111
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
120 A8	1400	40	Drive Wheel	4,00	
132 A8	2000	40	Free Rolling	4,00	