

## TYRES

Product group	Tyres
Item number	10000958
Valid tyre size	VF 420 / 95 R 34
LI / SI / PR	157 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 354 +



Bohnenkamp  
■ ■ ● Moving Professionals

 **ALLIANCE**  
ENGINEERED TO KEEP YOU AHEAD

## Notes and features

- The Alliance Agriflex 354 is a row crop tyre with VF technology for tractors, self-propelled and towed field sprayers.
- As a VF tyre, it has 40% more load capacity at the same inflation pressure or the same load capacity at 40% lower inflation pressure compared with a standard tyre.
- This leads to optimal crop and soil protection.
- The tyre provides high traction and excellent self-cleaning properties thanks to the stronger and optimally shaped lugs.
- Its large contact area and steel belted construction also ensure traction and good ground pressure distribution.
- The tyre is characterised by durability, reduced fuel costs and ride comfort.

## Technical Informations

Item number	10000958
EAN	8903635049500
Valid tyre size	VF 420 / 95 R 34
LI / SI / PR	157 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 354 +
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	137,30
Recommended rim size	W14L
Permitted rim size	DW14L, W13
Maximum air pressure [bar].	1,60
Section width (mm)	419
Outer diameter of tyre [mm].	1662
Stat. radius (SLR) [mm]	731.2
Speed Radius Index (SRI)	800
Rolling circumference [mm].	4927
Contact area [cm <sup>2</sup> ]	1932.3
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 D	4125	65		1,60	