

TYRES

Product group	Tyres
Item number	10000966
Valid tyre size	520 / 70 R 38
LI / SI / PR	153 A8 / 150 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Agrimax Factor is a new type of 70 series radial tyre for tillage tractors.
- Its tractor pattern with extended lugs provides good ride comfort.
- The reduced lug angle allows for reduced rolling resistance.
- The large contact area ensures smooth running.
- The strong polyester carcass provides excellent lateral stability and steering response even at higher speeds.

Technical Informations

Item number	10000966
EAN	8903094070725
Valid tyre size	520 / 70 R 38
LI / SI / PR	153 A8 / 150 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor
Carcass properties	E-Ready
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	167,93
Recommended rim size	W16L
Permitted rim size	W15L, W18L
Maximum air pressure [bar].	1,60
Section width (mm)	516
Tread width (mm)	500
Outer diameter of tyre [mm].	1749
Stat. radius (SLR) [mm]	795
Speed Radius Index (SRI)	825
Rolling circumference [mm].	5239
Tread depth (mm)	53,0
Number of lugs	23x2
E-Ready	Yes

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A8	3650	40		1,60	
150 D	3350	65		1,60	