

## **TYRES**

| Product group   | Tyres            |  |
|-----------------|------------------|--|
| Item number     | 10000972         |  |
| Valid tyre size | VF 650 / 65 R 38 |  |
| LI / SI / PR    | 172 D / 169 E    |  |
| TL/TT           | TL               |  |
| Brand           | Trelleborg       |  |
| Tread pattern   | TM1000PT         |  |



## Notes and features

- The Trelleborg TM1000 Progressive Traction is a VF tyre for high performance tractors.
- Compared to standard tyres, it offers up to 40% higher load capacity at the same air pressure or the same load capacity at 40% less air pressure.
- Its special lugs with double edge ensure very good grip and low slippage.
- The tyre offers very high load capacities, low soil compaction and excellent traction.



## **Technical Informations**

| Item number                  | 10000972         |
|------------------------------|------------------|
| EAN                          | 8059971028621    |
| Valid tyre size              | VF 650 / 65 R 38 |
| LI / SI / PR                 | 172 D / 169 E    |
| TL/TT                        | TL               |
| Brand                        | Trelleborg       |
| Tread pattern                | TM1000PT         |
| Antistatic                   | No               |
| Tyre colour                  | Black            |
| Nettogewicht [kg] (gültig)   | 266,04           |
| Recommended rim size         | DW23B            |
| Permitted rim size           | DW21B, TW23B     |
| Maximum air pressure [bar].  | 2,00             |
| Section width (mm)           | 670              |
| Outer diameter of tyre [mm]. | 1830             |
| Stat. radius (SLR) [mm]      | 800              |
| Speed Radius Index (SRI)     | 875              |
| Rolling circumference [mm].  | 5480             |
| E-Ready                      | No               |

## **Load capacity**

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 172 D | 6300               | 65           |               | 2,00                        |              |
| 169 E | 5800               | 70           |               | 2,00                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.