

## TYRES

Product group	Tyres
Item number	10000975
Valid tyre size	340 / 80 R 20
LI / SI / PR	144 A8 / 144 B
TL/TT	TL
Brand	Alliance
Tread pattern	585



## Notes and features

- The Alliance 585 was developed for telehandlers, backhoe and compact loaders.
- It is suitable for use in agriculture as well as on construction sites.
- The large, non-directional tread pattern provides good traction and great performance even on hard surfaces.
- The high tread depth guarantees a long tyre life and good protection against tyre damage.

## Technical Informations

Item number	10000975
EAN	8903635046288
Valid tyre size	340 / 80 R 20
Alternative size 1	12.5R20
LI / SI / PR	144 A8 / 144 B
TL/TT	TL
Brand	Alliance
Tread pattern	585
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	61,21
Recommended rim size	11
Permitted rim size	W11, W10
Maximum air pressure [bar].	4,00
Section width (mm)	343
Outer diameter of tyre [mm].	1052
Stat. radius (SLR) [mm]	472
Speed Radius Index (SRI)	525
Rolling circumference [mm].	3126
Contact area [cm <sup>2</sup> ]	774.2
Tread depth (mm)	29,0
Number of lugs	24x2
Guarantee period	5 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 A8	2800	40		4,00	
144 B	2800	50		4,00	