

TYRES

Product group	Tyres
Item number	10000976
Valid tyre size	400 / 80 R 24
LI / SI / PR	162 A8 / 162 B
TL/TT	TL
Brand	Alliance
Tread pattern	585



Notes and features

- The Alliance 585 was developed for telehandlers, backhoe and compact loaders.
- It is suitable for use in agriculture as well as on construction sites.
- The large, non-directional tread pattern provides good traction and great performance even on hard surfaces.
- The high tread depth guarantees a long tyre life and good protection against tyre damage.

Technical Informations

Item number	10000976
EAN	8903635046677
Valid tyre size	400 / 80 R 24
Alternative size 1	14.9R24
LI / SI / PR	162 A8 / 162 B
TL/TT	TL
Brand	Alliance
Tread pattern	585
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	106,10
Recommended rim size	DW13
Permitted rim size	W12, W13, W14L, DW12, DW14L
Maximum air pressure [bar].	5,00
Section width (mm)	404
Outer diameter of tyre [mm].	1250
Stat. radius (SLR) [mm]	567.1
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3752
Contact area [cm ²]	1028.7
Tread depth (mm)	33,0
Number of lugs	26x2
Tyre capacity 75% [ltr.]	180.15
Guarantee period	5 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	40		5,00	
162 B	4750	50		5,00	