

TYRES

Product group	Tyres
Item number	10000977
Valid tyre size	540 / 70 R 24
LI / SI / PR	168 A8 / 168 B
TL/TT	TL
Brand	Alliance
Tread pattern	585



Notes and features

- The Alliance 585 was developed for telehandlers, backhoe and compact loaders.
- It is suitable for use in agriculture as well as on construction sites.
- The large, non-directional tread pattern provides good traction and great performance even on hard surfaces.
- The high tread depth guarantees a long tyre life and good protection against tyre damage.

Technical Informations

Item number	10000977
EAN	8903635046318
Valid tyre size	540 / 70 R 24
LI / SI / PR	168 A8 / 168 B
TL/TT	TL
Brand	Alliance
Tread pattern	585
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	131,80
Recommended rim size	DW18L
Permitted rim size	DW16L
Maximum air pressure [bar].	4,00
Section width (mm)	540
Outer diameter of tyre [mm].	1366
Stat. radius (SLR) [mm]	598.4
Speed Radius Index (SRI)	650
Rolling circumference [mm].	4080
Contact area [cm ²]	1962.9
Tread depth (mm)	34,0
Number of lugs	24x2
Guarantee period	5 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A8	5600	40		4,00	
169 B	5800	50		4,00	