

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 10000977 |
| Valid tyre size | 540 / 70 R 24 |
| LI / SI / PR | 168 A8 / 168 B |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 585 |



Notes and features

- The Alliance 585 was developed for telehandlers, backhoe and compact loaders.
- It is suitable for use in agriculture as well as on construction sites.
- The large, non-directional tread pattern provides good traction and great performance even on hard surfaces.
- The high tread depth guarantees a long tyre life and good protection against tyre damage.

Technical Informations

| | |
|---------------------------------|----------------|
| Item number | 10000977 |
| EAN | 8903635046318 |
| Valid tyre size | 540 / 70 R 24 |
| LI / SI / PR | 168 A8 / 168 B |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 585 |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 131,80 |
| Recommended rim size | DW18L |
| Permitted rim size | DW16L |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 540 |
| Outer diameter of tyre [mm]. | 1366 |
| Stat. radius (SLR) [mm] | 598 |
| Speed Radius Index (SRI) | 650 |
| Rolling circumference [mm]. | 4080 |
| Contact area [cm ²] | 1962.9 |
| Tread depth (mm) | 34,0 |
| Number of lugs | 24x2 |
| Guarantee period | 5 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 168 A8 | 5600 | 40 | | 4,00 | |
| 168 B | 5600 | 50 | | 4,00 | |