

TYRES

Product group	Tyres
Item number	10000978
Valid tyre size	480 / 80 R 26
LI / SI / PR	167 A8 / 167 B
TL/TT	TL
Brand	Alliance
Tread pattern	585



Notes and features

- The Alliance 585 was developed for telehandlers, backhoe and compact loaders.
- It is suitable for use in agriculture as well as on construction sites.
- The large, non-directional tread pattern provides good traction and great performance even on hard surfaces.
- The high tread depth guarantees a long tyre life and good protection against tyre damage.

Technical Informations

Item number	10000978
EAN	8903635046783
Valid tyre size	480 / 80 R 26
LI / SI / PR	167 A8 / 167 B
TL/TT	TL
Brand	Alliance
Tread pattern	585
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	128,20
Recommended rim size	W15L
Permitted rim size	W16L, DW16L
Maximum air pressure [bar].	4,00
Section width (mm)	484
Outer diameter of tyre [mm].	1428
Stat. radius (SLR) [mm]	641.2
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4258
Contact area [cm ²]	1688.2
Tread depth (mm)	33,0
Number of lugs	26x2
Tyre capacity 75% [litr.]	308.47
Guarantee period	5 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 A8	5450	40		4,00	
167 B	5450	50		4,00	