

TYRES

Product group	Tyres
Item number	10000979
Valid tyre size	440 / 80 R 28
LI / SI / PR	163 A8 / 163 B
TL/TT	TL
Brand	Alliance
Tread pattern	585



Notes and features

- The Alliance 585 was developed for telehandlers, backhoe and compact loaders.
- It is suitable for use in agriculture as well as on construction sites.
- The large, non-directional tread pattern provides good traction and great performance even on hard surfaces.
- The high tread depth guarantees a long tyre life and good protection against tyre damage.

Technical Informations

Item number	10000979
EAN	8903635046325
Valid tyre size	440 / 80 R 28
Alternative size 1	16.9R28
LI / SI / PR	163 A8 / 163 B
TL/TT	TL
Brand	Alliance
Tread pattern	585
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	120,90
Recommended rim size	DW14L
Permitted rim size	DW13L, DW15L
Maximum air pressure [bar].	4,00
Section width (mm)	441
Outer diameter of tyre [mm].	1415
Stat. radius (SLR) [mm]	632.7
Speed Radius Index (SRI)	675
Rolling circumference [mm].	4276
Contact area [cm ²]	1476
Tread depth (mm)	33,0
Number of lugs	26x2
Guarantee period	5 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
163 A8	4875	40		4,00	
163 B	4875	50		4,00	