

TYRES

Product group	Tyres
Item number	10000982
Valid tyre size	VF 320 / 90 R 50 CFO
LI / SI / PR	166 D / 162 E
TL/TT	TL
Brand	Michelin
Tread pattern	SprayBib



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- The Michelin Spraybib is a tyre for field sprayers and similar vehicles.
- It provides high load capacities compared with the Agribib Row Crop at high speeds of up to 65 km/h.
- Thanks to its large contact area, the traction is increased and at the same time the soil is optimally protected.
- Due to its reinforced tread lugs, the tyre is particularly durable.

Technical Informations

Item number	10000982
EAN	3528708400405
Valid tyre size	VF 320 / 90 R 50 CFO
LI / SI / PR	166 D / 162 E
TL/TT	TL
Brand	Michelin
Tread pattern	SprayBib
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	135,00
Recommended rim size	DW11
Permitted rim size	DW10, W10, W11
Maximum air pressure [bar].	4,40
Section width (mm)	323
Outer diameter of tyre [mm].	1849
Stat. radius (SLR) [mm]	865
Rolling circumference [mm].	5545
Tread depth (mm)	39,0
Number of lugs	33x2
Tyre capacity 75% [ltr.]	226
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 D	5300	65		4,40	
162 E	4750	70		4,40	