

TYRES

Product group	Tyres	
Item number	10000983	
Valid tyre size	VF 710 / 60 R 46 CFO	
LI / SI / PR	186 D / 182 E	
TL/TT	TL	
Brand	Michelin	
Tread pattern	SprayBib	





Notes and features

- The Michelin Spraybib is a tyre for field sprayers and similar vehicles.
- It provides high load capacities compared with the Agribib Row Crop at high speeds of up to 65 km/h.
- Thanks to its large contact area, the traction is increased and at the same time the soil is optimally protected.
- Due to its reinforced tread lugs, the tyre is particularly durable.



Technical Informations

Item number	10000983
EAN	3528705748012
Valid tyre size	VF 710 / 60 R 46 CFO
LI / SI / PR	186 D / 182 E
TL/TT	TL
Brand	Michelin
Tread pattern	SprayBib
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	277,00
Recommended rim size	DW25B(A)
Maximum air pressure [bar].	3,20
Section width (mm)	722
Outer diameter of tyre [mm].	2002
Stat. radius (SLR) [mm]	900
Rolling circumference [mm].	5948
Tread depth (mm)	43,0
Number of lugs	24x2
Tyre capacity 75% [ltr.]	757
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
186 D	9500	65		3,20	
182 E	8500	70		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.