

TYRES

Product group	Tyres
Item number	10000986
Valid tyre size	VF 540 / 65 R 30
LI / SI / PR	158 D / 155 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1000PT



Bohnenkamp
Moving Professionals


TRELLEBORG

Notes and features

- The Trelleborg TM1000 Progressive Traction is a VF tyre for high performance tractors.
- Its special lugs with double edge ensure very good grip and low slippage.
- Compared to standard tyres, it offers up to 40% higher load capacity at the same air pressure or the same load capacity at 40% less air pressure.
- The tyre offers very high load capacities, low soil compaction and excellent traction.

Technical Informations

Item number	10000986
EAN	8059971028607
Valid tyre size	VF 540 / 65 R 30
LI / SI / PR	158 D / 155 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1000PT
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	143,00
Recommended rim size	W18L
Permitted rim size	DW18L, TW18L, DW16L
Maximum air pressure [bar].	2,00
Section width (mm)	540
Outer diameter of tyre [mm].	1480
Stat. radius (SLR) [mm]	635
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4450
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 D	4250	65		2,00	
155 E	3875	70		2,00	