Bohnenkamp Moving Professionals

05.02.2025

RIMS

Product group	Rims
Item number	10000988
Valid rim size	14 x 25
Rim connection	12/371/425
Bolt hole design	A3
Rim colour	Yellow
Brand	Jantsa



Technical Informations

Load capacity of rim 1 [kg]	4500
Speed Rims 1 [km/h]	25
Maximum speed [km/h].	25
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	95,00
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim material	steel
RAL	RAL1018
Cavity Sealed	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

05.	02	.20)25

Disc thickness [mm]	14
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	12
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	371
Bolt hole circle diameter [mm]	425
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.