

## WHEELS

Product group	Wheels
Item number	10000989
Valid wheel size	11.00 R 20
Brand	BKT
Tread pattern	Liftmax LM 81
Valid rim size	8.0 - 20
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Black
Load capacity complete wheel [kg]	6000
Speed complete wheel [km/h]	25



## Technical Informations

Assembly Item no. Tyres	• 15776032
LI / SI / PR	170 A5
Load capacity 1 [kg]	6000
Speed 1 [km/h].	25
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	160,47
ECE regulation number	not necessary
Section width (mm)	288
Tread depth (mm)	37,0
E-Ready	No

Assembly Item no. Rim	• 10000963
Load capacity of rim 1 [kg]	7500
Speed Rims 1 [km/h]	25
Maximum speed [km/h].	25
Maximum air pressure [bar].	10,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	mehrteilig
Quantity multi-piece	four-part
Rim material	steel
RAL	RAL9011
Cavity Sealed	No
Disc thickness [mm]	14.0
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole diameter [mm]	27.0
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	16x95
Preassembled valve	No