

TYRES

Product group	Tyres
Item number	10000996
Valid tyre size	9.5 R 17.5
LI / SI / PR	143 / 141 J, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SAR1



 **SAILUN**
TYRE

Notes and features

- The Sailun SAR1 is a tyre for steer and trailer axles in regional transport.
- Its extra wide grooves and tread sipes provide good grip on rain-soaked road surfaces.
- The particularly wide and firm tyre shoulder and the robust rubber compound enable slow and even wear.
- Thanks to its flat tread pattern design, the rolling resistance and thus the fuel consumption is reduced.

Technical Informations

Item number	10000996
EAN	6959655477016
Valid tyre size	9.5 R 17.5
LI / SI / PR	143 / 141 J, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SAR1
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/TR
Rolling resistance	D
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	31,96
Recommended rim size	6.75
Permitted rim size	6
Maximum air pressure [bar].	8,75
Section width (mm)	240
Outer diameter of tyre [mm].	842
Stat. radius (SLR) [mm]	391.19
Rolling circumference [mm].	2568
Tread depth (mm)	13,5

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 J	2725	100	Single	8,75	
141 J	2575	100	Twin	8,75	