

TYRES

Product group	Tyres
Item number	10001018
Valid tyre size	440 / 80 R 28
LI / SI / PR	156 A8 / 156 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TH400



Bohnenkamp
■ ■ ● Moving Professionals


TRELLEBORG

Notes and features

- Agro-industrial tyre for telescopic handlers, excavators and skid steer loaders.
- Ideal for use on hard ground and in biogas plants.
- Allows high machine stability, even when boom is fully extended.
- Maximum resistance to punctures and cuts.

Technical Informations

Item number	10001018
EAN	8059971024470
Valid tyre size	440 / 80 R 28
Alternative size 1	16.9R28
LI / SI / PR	156 A8 / 156 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TH400
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	113,42
Recommended rim size	14
Permitted rim size	15
Maximum air pressure [bar].	3,20
Section width (mm)	457
Outer diameter of tyre [mm].	1418
Stat. radius (SLR) [mm]	633
Rolling circumference [mm].	4295
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A8	4000	40		3,20	
156 B	4000	50		3,20	