

## **TYRES**

Product group	Tyres	
Item number	10001038	
Valid tyre size	600 / 50 R 22.5	
LI / SI / PR	159 D TL	
TL/TT		
Brand	Trelleborg	
Tread pattern	Twin Radial	





## Notes and features

- Excellent soil protection thanks to its large contact area and rounded shoulders.
- The structure of the lugs and the block tread pattern provide good traction as well as fast and effective selfcleaning.
- High performance in the field and on the road.
- Great ride comfort with low noise generation.



## **Technical Informations**

Item number	10001038
EAN	8059971031072
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	159 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	Twin Radial
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	108,78
Recommended rim size	20.00
Maximum air pressure [bar].	4,50
Section width (mm)	600
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	530
Rolling circumference [mm].	3550
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 D	4375	65		4,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.