

## TYRES

|                 |                        |
|-----------------|------------------------|
| Product group   | Tyres                  |
| Item number     | 10001040               |
| Valid tyre size | 750 / 55 - 26.5        |
| LI / SI / PR    | 190 A2 / 182 A8, 24 PR |
| TL/TT           | TT                     |
| Brand           | Trelleborg             |
| Tread pattern   | T440                   |



## Notes and features

- The Trelleborg Twin Forestry T440 is a forestry tyre for use on forestry tractors.
- Its tractor tread pattern with clod-breaking edges between the lugs ensures very good self-cleaning and excellent traction on clay, mud, ice and snow.
- Lugs with transverse edges and reinforced tyre shoulders enable efficient use of the tyre with belts.

**Technical Informations**

|                              |                        |
|------------------------------|------------------------|
| Item number                  | 10001040               |
| EAN                          | 8059971026344          |
| Valid tyre size              | 750 / 55 - 26.5        |
| LI / SI / PR                 | 190 A2 / 182 A8, 24 PR |
| TL/TT                        | TT                     |
| Brand                        | Trelleborg             |
| Tread pattern                | T440                   |
| TRA Code                     | LS-2                   |
| Carcass properties           | Steel Belted           |
| Antistatic                   | No                     |
| Tyre colour                  | Black                  |
| Nettogewicht [kg] (gültig)   | 291,93                 |
| Recommended rim size         | AG24.00                |
| Maximum air pressure [bar].  | 6,00                   |
| Section width (mm)           | 750                    |
| Outer diameter of tyre [mm]. | 1485                   |
| Stat. radius (SLR) [mm]      | 690                    |
| Speed Radius Index (SRI)     | 700                    |
| Rolling circumference [mm].  | 4485                   |
| Tread depth (mm)             | 46,0                   |
| Number of lugs               | 19x2                   |
| Tyre capacity 75% [ltr.]     | 320                    |
| E-Ready                      | No                     |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 190 A2 | 10600              | 10           |               | 6,00                     |              |
| 182 A8 | 8500               | 40           |               | 6,00                     |              |