

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 10001042 |
| Valid tyre size | 400 / 70 R 18 |
| LI / SI / PR | 147 A8 / 147 B |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TH400 |



Bohnenkamp
■ ■ ● Moving Professionals


TRELLEBORG

Notes and features

- Agro-industrial tyre for telescopic handlers, excavators and skid steer loaders.
- Ideal for use on hard ground and in biogas plants.
- Allows high machine stability, even when boom is fully extended.
- Maximum resistance to punctures and cuts.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 10001042 |
| EAN | 8059971024401 |
| Valid tyre size | 400 / 70 R 18 |
| Alternative size 1 | 15.5/70R18 |
| LI / SI / PR | 147 A8 / 147 B |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TH400 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 64,43 |
| Recommended rim size | 13 |
| Permitted rim size | 12 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 403 |
| Outer diameter of tyre [mm]. | 1010 |
| Stat. radius (SLR) [mm] | 450 |
| Rolling circumference [mm]. | 3040 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 147 A8 | 3075 | 40 | | 4,00 | |
| 147 B | 3075 | 50 | | 4,00 | |