

## TYRES

|                 |                |
|-----------------|----------------|
| Product group   | Tyres          |
| Item number     | 10001046       |
| Valid tyre size | 230 / 95 R 32  |
| LI / SI / PR    | 128 A8 / 128 B |
| TL/TT           | TL             |
| Brand           | Trelleborg     |
| Tread pattern   | TM100          |



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- Particularly suitable for work on row crops.
- Good ride comfort.
- Narrow radial tyre.

## Technical Informations

|                              |                |
|------------------------------|----------------|
| Item number                  | 10001046       |
| EAN                          | 8059971030938  |
| Valid tyre size              | 230 / 95 R 32  |
| LI / SI / PR                 | 128 A8 / 128 B |
| TL/TT                        | TL             |
| Brand                        | Trelleborg     |
| Tread pattern                | TM100          |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | not necessary  |
| Nettogewicht [kg] (gültig)   | 46,60          |
| Recommended rim size         | 7              |
| Permitted rim size           | 6              |
| Maximum air pressure [bar].  | 4,00           |
| Section width (mm)           | 235            |
| Outer diameter of tyre [mm]. | 1265           |
| Stat. radius (SLR) [mm]      | 595            |
| Rolling circumference [mm].  | 3900           |
| Tread depth (mm)             | 33,0           |
| Number of lugs               | 21x2           |
| Lug width (mm)               | 29             |
| E-Ready                      | No             |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 128 A8 | 1800               | 40           |               | 4,00                     |              |
| 128 B  | 1800               | 50           |               | 4,00                     |              |