

TYRES

Product group	Tyres
Item number	10001048
Valid tyre size	420 / 85 R 28
LI / SI / PR	139 A8 / 136 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600



Bohnenkamp
Moving Professionals



Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

Technical Informations

Item number	10001048
EAN	8059971004663
Valid tyre size	420 / 85 R 28
Alternative size 1	16.9R28
LI / SI / PR	139 A8 / 136 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	99,50
Recommended rim size	15
Permitted rim size	14
Maximum air pressure [bar].	1,60
Section width (mm)	438
Outer diameter of tyre [mm].	1425
Stat. radius (SLR) [mm]	635
Rolling circumference [mm].	4290
Tread depth (mm)	46,0
Number of lugs	19x2
Lug width (mm)	46
Tyre capacity 75% [litr.]	314
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
139 A8	2430	40		1,60	
136 B	2240	50		1,60	