

TYRES

Product group	Tyres
Item number	10001049
Valid tyre size	380 / 85 R 28
LI / SI / PR	133 A8 / 130 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600



Bohnenkamp
Moving Professionals



TRELLEBORG

Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

Technical Informations

Item number	10001049
EAN	8059971004632
Valid tyre size	380 / 85 R 28
Alternative size 1	14.9R28
LI / SI / PR	133 A8 / 130 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	79,00
Recommended rim size	13
Permitted rim size	12, 11
Maximum air pressure [bar].	1,60
Section width (mm)	390
Outer diameter of tyre [mm].	1357
Stat. radius (SLR) [mm]	615
Rolling circumference [mm].	4085
Tread depth (mm)	45,0
Number of lugs	19x2
Lug width (mm)	41
Tyre capacity 75% [ltr.]	239
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 A8	2060	40		1,60	
130 B	1900	50		1,60	