

## TYRES

Product group	Tyres
Item number	10001051
Valid tyre size	340 / 85 R 28
LI / SI / PR	127 A8 / 124 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600



Bohnenkamp  
Moving Professionals

  
**TRELLEBORG**

## Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

**Technical Informations**

Item number	10001051
EAN	8059971004595
Valid tyre size	340 / 85 R 28
Alternative size 1	13.6R28
LI / SI / PR	127 A8 / 124 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	67,40
Recommended rim size	12
Permitted rim size	11
Maximum air pressure [bar].	1,60
Section width (mm)	353
Outer diameter of tyre [mm].	1289
Stat. radius (SLR) [mm]	595
Rolling circumference [mm].	3885
Tread depth (mm)	44,0
Number of lugs	20x2
Lug width (mm)	36
Tyre capacity 75% [ltr.]	182
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
127 A8	1750	40		1,60	
124 B	1600	50		1,60	