

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 10001051 |
| Valid tyre size | 340 / 85 R 28 |
| LI / SI / PR | 127 A8 / 124 B |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM600 |



Bohnenkamp
Moving Professionals


TRELLEBORG

Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 10001051 |
| EAN | 8059971004595 |
| Valid tyre size | 340 / 85 R 28 |
| Alternative size 1 | 13.6R28 |
| LI / SI / PR | 127 A8 / 124 B |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM600 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 67,40 |
| Recommended rim size | 12 |
| Permitted rim size | 11 |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 353 |
| Outer diameter of tyre [mm]. | 1289 |
| Stat. radius (SLR) [mm] | 595 |
| Rolling circumference [mm]. | 3885 |
| Tread depth (mm) | 44,0 |
| Number of lugs | 20x2 |
| Lug width (mm) | 36 |
| Tyre capacity 75% [ltr.] | 182 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 127 A8 | 1750 | 40 | | 1,60 | |
| 124 B | 1600 | 50 | | 1,60 | |