

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 10001055 |
| Valid tyre size | 380 / 85 R 24 |
| LI / SI / PR | 131 A8 / 128 B |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM600 |



Bohnenkamp
Moving Professionals


TRELLEBORG

Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 10001055 |
| EAN | 8059971004526 |
| Valid tyre size | 380 / 85 R 24 |
| Alternative size 1 | 14.9R24 |
| LI / SI / PR | 131 A8 / 128 B |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM600 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 69,40 |
| Recommended rim size | 13 |
| Permitted rim size | 11, 12 |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 390 |
| Outer diameter of tyre [mm]. | 1256 |
| Stat. radius (SLR) [mm] | 560 |
| Rolling circumference [mm]. | 3750 |
| Tread depth (mm) | 45,0 |
| Number of lugs | 18x2 |
| Lug width (mm) | 37 |
| Tyre capacity 75% [litr.] | 215 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 131 A8 | 1950 | 40 | | 1,60 | |
| 128 B | 1800 | 50 | | 1,60 | |