

TYRES

Product group	Tyres
Item number	10001061
Valid tyre size	280 / 85 R 24
LI / SI / PR	115 A8 / 112 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600



Bohnenkamp
Moving Professionals



Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

Technical Informations

Item number	10001061
EAN	8059971013269
Valid tyre size	280 / 85 R 24
Alternative size 1	11.2R24
LI / SI / PR	115 A8 / 112 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	43,60
Recommended rim size	10
Permitted rim size	8, 9
Maximum air pressure [bar].	1,60
Section width (mm)	292
Outer diameter of tyre [mm].	1086
Stat. radius (SLR) [mm]	494
Rolling circumference [mm].	3276
Tread depth (mm)	39,0
Number of lugs	21x2
Lug width (mm)	27
Tyre capacity 75% [ltr.]	98
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
115 A8	1215	40		1,60	
112 B	1120	50		1,60	