

TYRES

Product group	Tyres
Item number	10001062
Valid tyre size	380 / 70 R 20
LI / SI / PR	122 A8 / 122 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700



Bohnenkamp
Moving Professionals


TRELLEBORG

Notes and features

- The TM 700 is an agricultural radial tyre.
- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.
- Top-level driving performance.

Technical Informations

Item number	10001062
EAN	8059971001518
Valid tyre size	380 / 70 R 20
LI / SI / PR	122 A8 / 122 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	54,80
Recommended rim size	12
Permitted rim size	11, 13
Maximum air pressure [bar].	1,60
Section width (mm)	370
Outer diameter of tyre [mm].	1088
Stat. radius (SLR) [mm]	485
Rolling circumference [mm].	3240
Tread depth (mm)	44,0
Lug width (mm)	32
Tyre capacity 75% [ltr.]	156
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
122 A8	1500	40		1,60	
122 B	1500	50		1,60	