

TYRES

Product group	Tyres
Item number	10001063
Valid tyre size	360 / 70 R 20
LI / SI / PR	120 A8 / 120 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700



Bohnenkamp
Moving Professionals


TRELLEBORG

Notes and features

- The TM 700 is an agricultural radial tyre.
- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.
- Top-level driving performance.

Technical Informations

Item number	10001063
EAN	8059971001488
Valid tyre size	360 / 70 R 20
LI / SI / PR	120 A8 / 120 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	46,80
Recommended rim size	11
Permitted rim size	10, 12
Maximum air pressure [bar].	1,60
Section width (mm)	352
Outer diameter of tyre [mm].	1038
Stat. radius (SLR) [mm]	464
Rolling circumference [mm].	3100
Tread depth (mm)	42,0
Number of lugs	17x2
Lug width (mm)	45
Tyre capacity 75% [ltr.]	128
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
120 A8	1400	40		1,60	
120 B	1400	50		1,60	