

TYRES

Product group	Tyres
Item number	10001064
Valid tyre size	300 / 70 R 20
LI / SI / PR	110 A8 / 110 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700



Bohnenkamp
Moving Professionals


TRELLEBORG

Notes and features

- The TM 700 is an agricultural radial tyre.
- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.
- Top-level driving performance.

Technical Informations

Item number	10001064
EAN	8059971001426
Valid tyre size	300 / 70 R 20
LI / SI / PR	110 A8 / 110 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	31,50
Recommended rim size	9
Permitted rim size	10
Maximum air pressure [bar].	1,60
Section width (mm)	286
Outer diameter of tyre [mm].	945
Stat. radius (SLR) [mm]	429
Rolling circumference [mm].	2805
Tread depth (mm)	37,0
Lug width (mm)	31
Tyre capacity 75% [litr.]	77.3
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
110 A8	1060	40		1,60	
110 B	1060	50		1,60	