

TYRES

Product group	Tyres
Item number	10001065
Valid tyre size	320 / 85 R 20
LI / SI / PR	119 A8 / 116 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600



Bohnenkamp
Moving Professionals



TRELLEBORG

Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

Technical Informations

Item number	10001065
EAN	8059971013238
Valid tyre size	320 / 85 R 20
Alternative size 1	12.4R20
LI / SI / PR	119 A8 / 116 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	46,00
Recommended rim size	11
Permitted rim size	9, 10
Maximum air pressure [bar].	1,60
Section width (mm)	329
Outer diameter of tyre [mm].	1052
Stat. radius (SLR) [mm]	470
Rolling circumference [mm].	3160
Tread depth (mm)	41,0
Lug width (mm)	30
Tyre capacity 75% [ltr.]	123
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
119 A8	1360	40		1,60	
116 B	1250	50		1,60	