

TYRES

Product group	Tyres
Item number	10001066
Valid tyre size	280 / 70 R 16
LI / SI / PR	112 A8 / 112 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700





Notes and features

- The TM 700 is an agricultural radial tyre.
- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.
- Top-level driving performance.



Technical Informations

Item number	10001066
EAN	8059971001365
Valid tyre size	280 / 70 R 16
LI / SI / PR	112 A8 / 112 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	24,30
Recommended rim size	9
Permitted rim size	8, 10
Maximum air pressure [bar].	2,40
Section width (mm)	282
Outer diameter of tyre [mm].	798
Stat. radius (SLR) [mm]	355
Rolling circumference [mm].	2385
Tread depth (mm)	35,0
Number of lugs	34x2
Lug width (mm)	34
Tyre capacity 75% [ltr.]	54.3
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
112 A8	1120	40		2,40	
112 B	1120	50		2,40	