

TYRES

Product group	Tyres	
Item number	10001070	
Valid tyre size	380 / 75 R 20	
LI / SI / PR	148 A8 / 148 B	
TL/TT	TL	
Brand	Michelin	
Tread pattern	XMCL	
Sonderpostenkategorie	Disassambled	
type of damage	Dismounted	





Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
- Reinforced sidewalls.

- Solid lugs.
- Belt plies made from steel mesh.



Technical Informations

Item number	10001070
EAN	4040658108884
Valid tyre size	380 / 75 R 20
LI / SI / PR	148 A8 / 148 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL
Antistatic	No
Nettogewicht [kg] (gültig)	70,00
Recommended rim size	12
Permitted rim size	11
Maximum air pressure [bar].	4,00
Section width (mm)	384
Outer diameter of tyre [mm].	1070
Stat. radius (SLR) [mm]	481
Rolling circumference [mm].	3180
Tread depth (mm)	33,0
Number of lugs	18x2
Lug width (mm)	36
Tyre capacity 75% [ltr.]	136
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 A8	3150	40		4,00	
148 B	3150	50		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.