

TYRES

Product group	Tyres
Item number	10001071
Valid tyre size	460 / 70 R 24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL
Sonderpostenkategorie	Disassembled
type of damage	Dismounted



Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
- Reinforced sidewalls.
- Solid lugs.
- Belt plies made from steel mesh.

Technical Informations

Item number	10001071
EAN	4040658108914
Valid tyre size	460 / 70 R 24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL
Antistatic	No
Nettogewicht [kg] (gültig)	101,00
Recommended rim size	DW15Lx24
Permitted rim size	14x24, 16x24, DW14Lx24, DW16Lx24, TW14Lx24
Maximum air pressure [bar].	3,60
Outer diameter of tyre [mm].	1248
Rolling circumference [mm].	3709
Tread depth (mm)	36,0
Tyre capacity 75% [litr.]	218.3
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		3,60	
159 A8	4375	40		3,60	