

## WHEELS

Product group	Wheels
Item number	10001086
Valid wheel size	405 / 70 R 20
Brand	Alliance
Tread pattern	608
Valid rim size	14 x 20
Rim connection	8/221/275
Bolt hole design	B3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	3875
Speed complete wheel [km/h]	10



## Technical Informations

Assembly Item no. Tyres	• 15284921
LI / SI / PR	155 A2 / 143 B
Load capacity 1 [kg]	3875
Speed 1 [km/h].	10
Load capacity 2 [kg]	2725
Speed 2 [km/h].	50
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	99,75
ECE regulation number	ECE 106

Section width (mm)	407
Stat. radius (SLR) [mm]	491
Rolling circumference [mm].	3265
Tread depth (mm)	18,5
Number of lugs	24x2
E-Ready	No
Assembly Item no. Rim	• 31610341
Load capacity of rim 1 [kg]	3900
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,72
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221

---

<b>Bolt hole circle diameter [mm]</b>	275
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V5.01.1
<b>Valve length [mm]</b>	50.0
<b>Valve angle [°]</b>	gerade