

WHEELS

| | |
|-----------------------------------|---------------|
| Product group | Wheels |
| Item number | 10001086 |
| Valid wheel size | 405 / 70 R 20 |
| Brand | Alliance |
| Tread pattern | 608 |
| Valid rim size | 14 x 20 |
| Rim connection | 8/221/275 |
| Bolt hole design | B3 |
| Offset (mm) | -50 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 3875 |
| Speed complete wheel [km/h] | 10 |
| Nettogewicht [kg] (gültig) | 99,75 |
| RDRA (Reifendruckregelanlage) | No |
| RDKS (Reifendruckkontrollsystem) | No |



Technical Informations

| | |
|-----------------------------|----------------|
| Assembly Item no. Tyres | • 15284921 |
| LI / SI / PR | 155 A2 / 143 B |
| Load capacity 1 [kg] | 3875 |
| Speed 1 [km/h]. | 10 |
| Load capacity 2 [kg] | 2725 |
| Speed 2 [km/h]. | 50 |
| Maximum air pressure [bar]. | 3,72 |
| TL/TT | TL |

| | |
|--------------------------------|-------------------------------|
| Tyre colour | Black |
| E-Ready | No |
| Carcass properties | Steel Belted |
| Antistatic | No |
| ECE regulation number | ECE 106 |
| Section width (mm) | 407 |
| Stat. radius (SLR) [mm] | 491 |
| Rolling circumference [mm]. | 3265 |
| Tread depth (mm) | 18,5 |
| Number of lugs | 24x2 |
| Assembly Item no. Rim | • 31610341 |
| Load capacity of rim 1 [kg] | 3900 |
| Speed Rims 1 [km/h] | 40 |
| Maximum speed [km/h]. | 40 |
| Type of drive | Angetriebene & gezogene Achse |
| Number of bolt holes | 8 |
| hub hole diameter [mm]. | 221 |
| Bolt hole circle diameter [mm] | 275 |
| Bolt hole diameter [mm] | 27 |
| Bolt hole design EUWA | B22 DS 36 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R18 |
| Rim centering | BC |
| Rim material | steel |
| RAL | RAL9006 |
| Valve seat | External Valve |
| Ventilation holes | No |

| | |
|--------------------------|-------------|
| Single / multi-part | einteilig |
| Hump | kein Hump |
| Valve protection | VSH |
| Cavity Sealed | No |
| Verschweißung beidseitig | No |
| Assembly Item no. Valve | • 47201038 |
| Preassembled valve | No |
| TPMS-kompatibles Ventil | No |
| Valve hole diameter [mm] | 15.7 |
| Valve design | Metal valve |
| Valve designation ETRTO | V5.01.1 |
| Valve length [mm] | 50.0 |
| Valve angle [°] | gerade |