

WHEELS

Product group	Wheels
Item number	10001087
Valid wheel size	405 / 70 R 20
Brand	Alliance
Tread pattern	608
Valid rim size	14 x 20
Rim connection	8/221/275
Bolt hole design	B3
Offset (mm)	-100
Rim colour	Silver
Load capacity complete wheel [kg]	3875
Speed complete wheel [km/h]	10
Nettogewicht [kg] (gültig)	109,88
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15284921
LI / SI / PR	155 A2 / 143 B
Load capacity 1 [kg]	3875
Speed 1 [km/h].	10
Load capacity 2 [kg]	2725
Speed 2 [km/h].	50
Maximum air pressure [bar].	3,72
TL/TT	TL

Tyre colour	Black
E-Ready	No
Carcass properties	Steel Belted
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	407
Stat. radius (SLR) [mm]	491
Rolling circumference [mm].	3265
Tread depth (mm)	18,5
Number of lugs	24x2
Assembly Item no. Rim	• 31610342
Load capacity of rim 1 [kg]	3900
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 DS 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No

Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Air-water valve
Valve length [mm]	47
Valve angle [°]	gerade
Valve cap Material	Plastic
Colour of cap	Black