

## RIMS

Product group	Rims
Item number	10001106
Valid rim size	11.75 x 22.5
Rim connection	10/281/335
Bolt hole design	M22
Offset (mm)	+120
Half centre distance (HMA) [mm]	133.5
Rim colour	Black
Brand	Covex



## Technical Informations

Load capacity of rim 1 [kg]	7500
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	5000
Speed Rims 2 [km/h]	100
Maximum speed [km/h].	100
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	42,50
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9005

---

Cavity Sealed	No
Disc thickness [mm]	13.5
Verschweißung beidseitig	No
Ventilation holes	Yes
Rim centering	HB
Number of bolt holes	10
Bolt hole diameter [mm]	26
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation	58 MS
Valve designation ETRTO	V3.22.1
Valve length [mm]	58.0
Valve angle [°]	45
Valve cap Material	Steel