

RIMS

| | |
|------------------|-------------|
| Product group | Rims |
| Item number | 10001107 |
| Valid rim size | 6.75 x 17.5 |
| Rim connection | 6/161/205 |
| Bolt hole design | B2 |
| Rim colour | Black |
| Brand | Covex |



Technical Informations

| | |
|-----------------------------|-------------------------------|
| Load capacity of rim 1 [kg] | 3135 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 2100 |
| Speed Rims 2 [km/h] | 100 |
| Maximum speed [km/h]. | 100 |
| Type of drive | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig) | 26,50 |
| Hump | kein Hump |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9005 |

| | |
|--------------------------------|----------------|
| Cavity Sealed | No |
| Disc thickness [mm] | 10 |
| Verschweißung beidseitig | No |
| Ventilation holes | No |
| Rim centering | BHC |
| Number of bolt holes | 6 |
| Bolt hole design EUWA | B18 DS 32 |
| Bolt hole diameter [mm] | 21.5 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R16 |
| hub hole diameter [mm]. | 161 |
| Bolt hole circle diameter [mm] | 205 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 9.7 |
| Preassembled valve | Yes |
| TPMS-kompatibles Ventil | No |
| Valve design | Metal valve |
| Valve designation ETRTO | V3.20.1 |
| Valve length [mm] | 41.0 |
| Valve cap Material | Steel |