

RIMS

Product group	Rims
Item number	10001111
Valid rim size	7.50 x 22.5
Rim connection	10/281/335
Bolt hole design	M22
Offset (mm)	+147
Half centre distance (HMA) [mm]	160
Rim colour	Black
Brand	Covex



Technical Informations

Load capacity of rim 1 [kg]	3250
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	35,00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9005
Colour type	Glossy
Cavity Sealed	No

Disc thickness [mm]	13
Verschweißung beidseitig	No
Ventilation holes	Yes
Rim centering	HB
Number of bolt holes	10
Bolt hole design EUWA	M22
Bolt hole diameter [mm]	26
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation	58 MS
Valve designation ETRTO	V3.22.1
Valve length [mm]	58.0
Valve angle [°]	45
Valve cap Material	Steel