

## RIMS

|                                 |             |
|---------------------------------|-------------|
| Product group                   | Rims        |
| Item number                     | 10001111    |
| Valid rim size                  | 7.50 x 22.5 |
| Rim connection                  | 10/281/335  |
| Bolt hole design                | M22         |
| Offset (mm)                     | +147        |
| Half centre distance (HMA) [mm] | 160         |
| Rim colour                      | Black       |
| Brand                           | Covex       |



## Technical Informations

|                             |                               |
|-----------------------------|-------------------------------|
| Load capacity of rim 1 [kg] | 3250                          |
| Speed Rims 1 [km/h]         | 100                           |
| Maximum speed [km/h].       | 100                           |
| Type of drive               | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig)  | 35,00                         |
| Hump                        | kein Hump                     |
| Single / multi-part         | einteilig                     |
| Rim material                | steel                         |
| RAL                         | RAL9005                       |
| Colour type                 | Glossy                        |
| Cavity Sealed               | No                            |

|                                |                |
|--------------------------------|----------------|
| Disc thickness [mm]            | 13             |
| Verschweißung beidseitig       | No             |
| Ventilation holes              | Yes            |
| Rim centering                  | HB             |
| Number of bolt holes           | 10             |
| Bolt hole design EUWA          | M22            |
| Bolt hole diameter [mm]        | 26             |
| hub hole diameter [mm].        | 281            |
| Bolt hole circle diameter [mm] | 335            |
| Valve seat                     | External Valve |
| Valve hole diameter [mm]       | 9.7            |
| Preassembled valve             | Yes            |
| TPMS-kompatibles Ventil        | No             |
| Valve design                   | Metal valve    |
| Valve designation              | 58 MS          |
| Valve designation ETRTO        | V3.22.1        |
| Valve length [mm]              | 58.0           |
| Valve angle [°]                | 45             |
| Valve cap Material             | Steel          |