

TYRES

Product group	Tyres
Item number	10001119
Valid tyre size	440 / 80 R 24
LI / SI / PR	161 A8 / 161 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TH400



Bohnenkamp
■ ■ ● Moving Professionals


TRELLEBORG

Notes and features

- Agro-industrial tyre for telescopic handlers, excavators and skid steer loaders.
- Ideal for use on hard ground and in biogas plants.
- Allows high machine stability, even when boom is fully extended.
- Maximum resistance to punctures and cuts.

Technical Informations

Item number	10001119
EAN	8059971024432
Valid tyre size	440 / 80 R 24
Alternative size 1	16.9R24
LI / SI / PR	161 A8 / 161 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TH400
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	100,03
Recommended rim size	14
Permitted rim size	15
Maximum air pressure [bar].	4,00
Section width (mm)	457
Outer diameter of tyre [mm].	1312
Stat. radius (SLR) [mm]	585
Rolling circumference [mm].	3975
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
161 A8	4625	40		4,00	
161 B	4625	50		4,00	