

TYRES

Product group	Tyres
Item number	10001120
Valid tyre size	340 / 80 R 18
LI / SI / PR	143 A8 / 143 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TH400



Bohnenkamp
■ ■ ● Moving Professionals



TRELLEBORG

Notes and features

- Agro-industrial tyre for telescopic handlers, excavators and skid steer loaders.
- Ideal for use on hard ground and in biogas plants.
- Allows high machine stability, even when boom is fully extended.
- Maximum resistance to punctures and cuts.

Technical Informations

Item number	10001120
EAN	8059971024395
Valid tyre size	340 / 80 R 18
Alternative size 1	12.5R18
LI / SI / PR	143 A8 / 143 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TH400
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	54,35
Recommended rim size	11
Permitted rim size	10, 12
Maximum air pressure [bar].	4,00
Section width (mm)	351
Outer diameter of tyre [mm].	994
Stat. radius (SLR) [mm]	440
Rolling circumference [mm].	3020
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 A8	2725	40		4,00	
143 B	2725	50		4,00	