

TYRES

Product group	Tyres
Item number	10001122
Valid tyre size	480 / 80 R 26
LI / SI / PR	160 A8 / 160 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TH400



Bohnenkamp
■ ■ ● Moving Professionals



TRELLEBORG

Notes and features

- Agro-industrial tyre for telescopic handlers, excavators and skid steer loaders.
- Ideal for use on hard ground and in biogas plants.
- Allows high machine stability, even when boom is fully extended.
- Maximum resistance to punctures and cuts.

Technical Informations

Item number	10001122
EAN	8059971024463
Valid tyre size	480 / 80 R 26
Alternative size 1	18.4R26
LI / SI / PR	160 A8 / 160 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TH400
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	117,72
Recommended rim size	15
Permitted rim size	16
Maximum air pressure [bar].	3,20
Section width (mm)	495
Outer diameter of tyre [mm].	1425
Stat. radius (SLR) [mm]	630
Rolling circumference [mm].	4315
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 A8	4500	40		3,20	
160 B	4500	50		3,20	