

TYRES

Product group	Tyres
Item number	10001126
Valid tyre size	VF 480 / 95 R 50
LI / SI / PR	170 A8 / 170 B
TL/TT	TL
Brand	Michelin
Tread pattern	YieldBib
Sonderpostenkategorie	DA



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Newly-developed tyre, especially for high-power tractors and self-propelled field sprayers used in row crops (corn, potatoes, etc.).
- Michelin Ultraflex Technology allows reduced inflation pressure by up to 40% with the same load capacity compared with standard radial tyres.
- Large contact area for reduced soil compaction and increased yield.
- Better traction due to R1W lugs with 45 degree lug angle enables reduced fuel consumption.
- Michelin Stubble Shield offers special protection against tread chunking and further impact damages caused by abrasive corn stubble.

Technical Informations

Item number	10001126
EAN	4040658109447
Valid tyre size	VF 480 / 95 R 50
LI / SI / PR	170 A8 / 170 B
TL/TT	TL
Brand	Michelin
Tread pattern	YieldBib
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	235,00
Recommended rim size	DW16A
Permitted rim size	DW15B, W15B, DW16B, W16B, DW15L
Maximum air pressure [bar].	1,60
Section width (mm)	477
Outer diameter of tyre [mm].	2186
Rolling circumference [mm].	6661
Tread depth (mm)	51,0
Tyre capacity 75% [ltr.]	593.25
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
170 A8	6000	40		1,60	
170 B	6000	50		1,60	