

TYRES

Product group	Tyres
Item number	10001131
Valid tyre size	420 / 65 R 30
LI / SI / PR	139 A8 / 136 A8
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax RT 657
Sonderpostenkategorie	Disassambled
type of damage	Dismounted





Notes and features

- The BKT Agrimax RT 657 is a wide tyre of the 65 series in the power range up to 250 hp.
- Due to the solid lugs and the large contact area, the tyre provides excellent traction even when working on the most difficult soils.
- At the same time, its high air volume and variable inflation pressure adjustment ensure optimum soil protection.
- On the road, the tyre guarantees high ride comfort combined with low rolling resistance and thus low fuel consumption.
- For road transport, the tyre is approved for speeds up to 65 km/h.



Technical Informations

Item number	10001131
EAN	4040658109492
Valid tyre size	420 / 65 R 30
LI / SI / PR	139 A8 / 136 A8
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 657
Antistatic	No
Nettogewicht [kg] (gültig)	81,50
Recommended rim size	W13
Permitted rim size	W12, W11
Maximum air pressure [bar].	2,40
Section width (mm)	418
Outer diameter of tyre [mm].	1308
Stat. radius (SLR) [mm]	606
Rolling circumference [mm].	3952
Tread depth (mm)	58,0
Number of lugs	24x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
139 A8	2430	40		2,40	
136 A8	2240	40		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.