

TYRES

Product group	Tyres
Item number	10001132
Valid tyre size	VF 710 / 60 R 42
LI / SI / PR	176 D / 173 E
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib 2
Sonderpostenkategorie	Disassambled
type of damage	Dismounted



Notes and features

- The Michelin Axiobib 2 is suitable for tractors from 160 hp up to 550 hp.
- The VF tyre with its Ultraflex technology enables increased load capacity by up to 40%.
- Furthermore, the tyre is characterised by its low inflation pressure and excellent traction in the field.



Technical Informations

Item number	10001132
EAN	4040658109508
Valid tyre size	VF 710 / 60 R 42
LI / SI / PR	176 D / 173 E
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib 2
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	314,00
Recommended rim size	DW25B
Permitted rim size	DW23(A)
Maximum air pressure [bar].	2,00
Section width (mm)	730
Outer diameter of tyre [mm].	1885
Stat. radius (SLR) [mm]	830
Rolling circumference [mm].	5574
Tread depth (mm)	58,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	710
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 D	7100	65		2,00	
173 E	6500	70		2,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.