Bohnenkamp Moving Professionals

05.02.2025

TYRES

Product group	Tyres
Item number	10001133
Valid tyre size	340 / 65 R 20
LI / SI / PR	127 A8 / 124 A8
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax RT 657
Sonderpostenkategorie	Disassambled
type of damage	Dismounted





Notes and features

- The BKT Agrimax RT 657 is a wide tyre of the 65 series in the power range up to 250 hp.
- Due to the solid lugs and the large contact area, the tyre provides excellent traction even when working on the most difficult soils.
- At the same time, its high air volume and variable inflation pressure adjustment ensure optimum soil protection.
- On the road, the tyre guarantees high ride comfort combined with low rolling resistance and thus low fuel consumption.
- For road transport, the tyre is approved for speeds up to 65 km/h.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10001133
EAN	4040658109515
Valid tyre size	340 / 65 R 20
LI / SI / PR	127 A8 / 124 A8
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax RT 657
Antistatic	No
Nettogewicht [kg] (gültig)	40,55
Recommended rim size	W11
Permitted rim size	W10, W12
Section width (mm)	343
Outer diameter of tyre [mm].	950
Stat. radius (SLR) [mm]	430
Rolling circumference [mm].	2892
Tread depth (mm)	30,0
Number of lugs	19x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
127 A8	1750	40			
124 A8	1600	40			

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.