

TYRES

Product group	Tyres
Item number	10001135
Valid tyre size	250 / 80 R 18
LI / SI / PR	125 A8 / 125 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	10001135
EAN	8903094066131
Valid tyre size	250 / 80 R 18
LI / SI / PR	125 A8 / 125 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	25,50
Recommended rim size	W8
Permitted rim size	W7, W9
Maximum air pressure [bar].	4,00
Section width (mm)	250
Outer diameter of tyre [mm].	835
Stat. radius (SLR) [mm]	375
Rolling circumference [mm].	2539
Tread depth (mm)	33,5
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
125 A8	1650	40		4,00	
125 B	1650	50		4,00	