

TYRES

Product group	Tyres
Item number	10001152
Valid tyre size	12.00 R 24
LI / SI / PR	178 A5
TL/TT	TL
Brand	BKT
Tread pattern	Liftmax LM 81
Sonderpostenkategorie	Remaining stock



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- The BKT Liftmax LM 81 is a newly-developed industrial radial tyre produced according to the latest technology for heavy forklifts and terminal tractors.
- The strong all-steel casing and reinforced sidewall provide excellent stability and handling in lift mode.
- Its aggressive and robust tread pattern and rubber compound provide excellent traction and a long service life.
- The radial casing absorbs ground unevenness and thus increases high ride comfort and the operator's safety and prevents fatigue.
- All Liftmax LM 81 are designed to dissipate static charge from the vehicle.

Technical Informations

Item number	10001152
EAN	4040658109683
Valid tyre size	12.00 R 24
LI / SI / PR	178 A5
TL/TT	TL
Brand	BKT
Tread pattern	Liftmax LM 81
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	124,31
Recommended rim size	8.5
Permitted rim size	9.0
Maximum air pressure [bar].	10,00
Section width (mm)	310
Outer diameter of tyre [mm].	1235
Tread depth (mm)	39,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178 A5	7500	25	Steering wheel	10,00	
	9750	25	Load wheel	10,00	